




Rohr zu Innengewinde

Aufschraubverschraubung, T-Form 180°

CRTF-N



Verbindung zölliger Rohre mit NPT Außengewinden

Bestell- nummer	Rohr AD D		T (NPT)	d min.	Schlüsselweite				A	B	ℓ	L	L ₁
	Zoll	mm			h		H						
					Zoll	mm	Zoll	mm					
CRTF 2 · 2N	1/8	3,17	1/8	2,28	9/16	14,28	7/16	11,11	12,70	15,24	18,03	24,63	19,05
CRTF 4 · 2N	1/4	6,35	1/8	4,82	9/16	14,28	9/16	14,28	15,24	17,78	19,55	26,92	19,05
CRTF 4 · 4N	1/4	6,35	1/4	4,82	11/16	17,46	9/16	14,28	15,24	17,78	22,35	29,71	22,35
CRTF 6 · 4N	3/8	9,52	1/4	7,11	11/16	17,46	11/16	17,46	16,76	19,30	23,87	31,24	22,35
CRTF 8 · 6N	1/2	12,70	3/8	10,41	13/16	20,63	7/8	22,22	22,86	21,84	25,90	36,06	22,35
CRTF 8 · 8N	1/2	12,70	1/2	10,41	1	25,40	7/8	22,22	22,86	21,84	28,70	38,86	28,44
CRTF 12 · 12N	3/4	19,05	3/4	15,74	1-3/8	34,92	1-1/8	28,57	24,38	21,84	34,54	44,70	31,75
CRTF 16 · 12N	1	25,40	3/4	22,35	1-3/8	34,92	1-1/2	38,10	31,24	26,41	36,83	49,02	31,75
CRTF 16 · 16N	1	25,40	1	22,35	1-11/16	42,86	1-1/2	38,10	31,24	26,41	41,40	53,59	38,10

Verbindung metrischer Rohre mit NPT Außengewinden

Bestell- nummer	Rohr AD D	T (NPT)	d min.	Schlüsselweite		A	B	ℓ	L	L ₁
				h	H					
CRTF 3M · 2N	3	1/8	2,4	12,7	12	12,9	15,3	18,0	24,7	19,0
CRTF 6M · 2N	6	1/8	4,8	14,0	14	15,3	17,7	19,6	27,0	19,0
CRTF 6M · 4N	6	1/4	4,8	17,5	14	15,3	17,7	22,4	29,8	22,4
CRTF 6M · 8N	6	1/2	4,8	25,4	14	15,3	17,7	27,2	34,5	28,4
CRTF 8M · 2N	8	1/8	6,3	15,8	16	16,2	18,6	22,4	29,9	19,0
CRTF 8M · 4N	8	1/4	6,3	17,5	16	16,2	18,6	23,1	30,6	22,4
CRTF 8M · 6N	8	3/8	6,3	20,6	16	16,2	18,6	25,2	32,4	22,4
CRTF 8M · 8N	8	1/2	6,3	25,4	16	16,2	18,6	28,0	35,2	28,4
CRTF 10M · 4N	10	1/4	7,9	17,5	19	17,2	19,5	25,0	32,6	22,4
CRTF 12M · 4N	12	1/4	9,5	20,6	22	22,8	22,0	25,9	36,0	22,4
CRTF 12M · 6N	12	3/8	9,5	20,6	22	22,8	22,0	25,9	36,0	22,4